

When creating a preliminary data sheet, there are not yet enough measured values and/or production runs available to determine statistically validated average/limit values. In individual cases, production repeatability is not yet ensured.

DuploCOLL® 90808.5 NP

Double-sided adhesive foam tape with a special developed high performance adhesive for BMW paint systems

Product construction			
	Name	Colour	Thickness [mm]
Liner	Siliconized paper	white	approx. 0,08
Adhesive covered side	High performance adhesive		
Carrier	Polyethylene foam	black	approx. 0,80
Adhesive open side	Pure acrylic		
Total thickness:			approx. 0,88

Product advantages

- The specially developed high performance adhesive is characterized by an excellent final adhesion, also on dirt-repellent and scratch-proof coating systems and outstanding shear strength; furthermore the adhesive shows good results after established ageing tests.
- The pure acrylic adhesive on the open side is characterized by very good temperature resistance. The adhesive has an adequate initial and very good final adhesion
- Good ageing- and weathering resistance
- DuploCOLL® NP is able to compensate component tolerances with its permanently flexible and compressible foam carrier.

Main application fields

- Permanent bonding of exterior parts on BMW clear coat according to category 2, 3 or 4 of GS 97109:2024-02 such as emblems & letterings, kickplates, water management elements, windscreen cover and PDC sensors.

Specific technical data*

Temperature range -40 °C to +95 °C**


* Specific test results, statistically not approved.

** Temperature range in climatic tests

DuploCOLL® 90808.5 NP

Double-sided adhesive foam tape with a special developed high performance adhesive for BMW paint systems

Technical Data			
Shear strength	on stainless steel +23 °C +/- 2°C	open side	80 N/625 mm ²
		covered side	60 N/625 mm ²
Peel strength 180°	on stainless steel at +23 °C +/- 2°C	open side	25 N/25 mm
		covered side	75 N/25 mm



Application

Recommended application temperature 18 °C to 35 °C

Application guidelines www.lohmann-tapes.com

Storage

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).
The storage stability is one year after delivery.

Product presentation

Converted product	Rolls	Spools
Width [mm]		
Length [m]		
Max. log width: 1260 mm	Other dimensions, die-cuts and sheets on request.	

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

IMPORTANT NOTE

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: May 2024

Lohmann GmbH & Co. KG
Irlicher Strasse 55
56567 Neuwied
Germany
Phone: + 49 (0) 26 31 34 - 0
Fax: + 49 (0) 26 31 34 - 6661
E-mail: info@lohmann-tapes.com

For further information
www.lohmann-tapes.com

 **Lohmann**
The Bonding Engineers