

When creating a preliminary data sheet, there are not yet enough measured values and/or production runs available to determine statistically validated average/limit values. In individual cases, production repeatability is not yet ensured.

## DuploCOLL® 91115.4 NP

**Double-sided adhesive foam tape with a special developed high performance adhesive for new paint systems**

Product construction			
	Name	Colour	Thickness [mm]
Liner	Polyethylene film	yellow	approx. 0,10
Adhesive covered side	High performance adhesive		
Carrier	Polyethylene foam	black	approx. 1,50
Adhesive open side	High performance adhesive		
<b>Total thickness:</b>			approx. 1,60

### Product advantages

- The specially developed high performance adhesive is characterized by an excellent final adhesion, also on dirt-repellent and scratch-proof coating systems and outstanding shear strength.
- The adhesive shows consistent results after established ageing tests in the automotive industry (heat, humidity, cold, etc.).
- DuploCOLL® NP with its compressible foam carrier is better in compensating component tolerances than hard foamed systems.

### Main application fields

- Permanent bonding of exterior parts, e.g. trim parts, door covers, wheel house covers, door sill panels or moldings, emblems and letterings

### Specific technical data\*

**Temperature range** -40 °C to +100 °C

# DuploCOLL® 91115.4 NP

Double-sided adhesive foam tape with a special developed high performance adhesive for new paint systems

Technical Data		
Shear strength	on stainless steel at +23 °C +/- 2°C	80 N/625 mm <sup>2</sup>
Peel strength	on stainless steel at +23 °C +/- 2°C	≥ 50 N/25 mm



Application	
Recommended application temperature	18 °C to 35 °C
Application guidelines	<a href="http://www.lohmann-tapes.com">www.lohmann-tapes.com</a>

Storage
Adhesive tapes should be stored at room temperature and normal humidity (50-70 %). The storage stability is one year after delivery.

Product presentation			
Converted product	Rolls		Spools
Width [mm]			
Length [m]			
Max. log width: 1260 mm	on request		

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

## IMPORTANT NOTE

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: February 2023

Lohmann GmbH & Co. KG  
 Irlicher Strasse 55  
 56567 Neuwied  
 Germany  
 Phone: + 49 (0) 26 31 34 - 0  
 Fax: + 49 (0) 26 31 34 - 6661  
 E-mail: [info@lohmann-tapes.com](mailto:info@lohmann-tapes.com)

For further information  
[www.lohmann-tapes.com](http://www.lohmann-tapes.com)

 **Lohmann**  
 The Bonding Engineers